

SOLID Bifacial

108 cell

Frameless_ Glass/Glass_Transparent



Self-cleaning
effect




Extreme load
resistance



Fire class A



Salt mist
resistance



Ammonia
resistance



35% of recycled
glass content



98% recyclable



Hail resistance
class 4



Positive sorting up to +5W

Front side ⚡ 435 W



Deutsches
Institut
für
Bautechnik

DIBt

30 Year
product
warranty



90% Power
warranty

30 Year
efficiency
warranty

Electrical data (STC*)	
Maximum power (W)	435
Cell technology	N type, TOPCon - bifacial
Open circuit voltage (V_{oc}/V)	38,92
Short circuit current (I_{sc}/A)	13,80
Max power voltage (V_{mpp}/V)	32,96
Max power current (I_{mpp}/A)	13,20
Module efficiency (η)	22,07%
Max system voltage (V)	1500
Max current (A)	25
Power tolerance	0/+5W

*Under standard test conditions (STC) of irradiance of 1000W/sq.m., spectrum AM1.5 and cell temperature of 25°C. Flash testing measurement accuracy of +/-5%.

Warranty	
30 years product warranty	
30 years efficiency warranty	
First year degradation (%)	1%
Annual degradation (%)	0,31%
Power in year 30 (%)	90%



Temperature ratings	
Current temperature coefficient (α)	+0.045% / °C
Voltage temperature coefficient (β)	-0.250% / °C
Power temperature coefficient (δ)	-0.300% / °C
Nominal operating module temperature	46 °C
Mechanical data	
Dimensions (LxWxH) (mm)	1729x1140x7,2
Dimensions with edge sealing (LxWxH) (mm)	1733±2x1144±2x7,2
Weight (kg)	32
Front glass (mm)	3,2 structured, low reflection, with AR coating, ESG
Back glass (mm)	3,2, transparent, ESG
Cell Size (mm)	182x91,875
Busbars	10
Cell configuration	6x18
Frame	Frameless
Rated operating altitude (m)	Up to 2000
Operating temperature (°C)	-40 ÷ +85
Maximum test load (wind/snow) (Pa)	5400/10500
Junction box / IP class	Split junction box / IP68
Cable cross section size (mm ²)	4
Cable length (m)	1,2
Bypass diodes	3
Connector	MC4-EVO2

Packing information	
Modules per pallet (pcs)	25
Dimensions of a pallet (LxWxH) (mm)	1860x1220x1100
Weight of a pallet (gross) (kg)	887
Pallets per 13,6 m truck (pcs)	22
Modules per 13,6 m truck (pcs)	550

Certifications	
IEC 61215:2021; IEC 61730:2023	
Cradle to Cradle (C2C)	Gold level
abZ/aBG	National technical approval/ General construction technique permit
IEC 62716:2013	Ammonia corrosion testing
IEC 61701:2020	Salt mist corrosion testing
IEC 61215-2:2021	40mm hailstone - Hail resistance class 4 (HW4)
ISO 9001:2015	Quality management systems
ISO 14001:2015	Environmental management systems
ISO 45001:2018	Occupational health and safety
SundaHus	A level assessment
Produced using 100% renewable energy	
Membership at Svensk Solenergi	



This datasheet is not legally binding. The manufacturer reserves the right to make changes to product specifications and / or product features without prior notice. The most recent versions of all documents (T&C's, datasheets, warranties and installation manuals) can always be found on our website at www.solitek.eu

